Labino[®] SuperXenon 35 & 50 w



DOCKING BATTERY | SUPER POWERFUL

MAKES IT BRIGHT

Labino[®] SuperXenon 50 W UV lamp is one of the most powerful handheld UV lamp on the market! The 50 W Xenon bulb offers an extremely high UV intensity, providing a very clear excitation of fluorescent material. This lamp makes it possible to search very large areas as you can use a floodlight reflector and still see excitations in daylight and at great distances. The SuperXenon is also available with a 35 W bulb if lower intensity is required.

The Labino[®] SuperXenon lamp contains the electronics and bulb in a single housing and is available with no handle, a pistol handle as well as a top handle. You can chose between three distinctions – floodlight, midlight or spotlight – each giving different beams and intensities.



This product can be operated by two different power systems – battery as well as via a PSU. The battery is a docking battery. You can easily replace to a new battery and charge the used one separate from the light. You can also switch between a battery and mains power supply unit (PSU) on the same lamp by switching the docking devices – both fit to the same lamp. The Labino[®] SuperXenon lamp obtains full power in 5-15 seconds and can be switched on and off whenever used, without pre-cooling and it is unaffected by magnetic fields. Manufactured in Sweden.

TECHNICAL SPECIFICATIONS:

Floodlight

Distribution angle (beam) approx. 45° Irradiance: 50w bulb \approx 5 800 µW/cm²=at 38 cm (15") 35w bulb \approx 4 000 µW/cm²=at 38 cm (15")

Visible light 50w: < 2 Lux Visible light 35w: < 2 Lux

Midlight

Distribution angle (beam) approx. 20° Irradiance: 50w bulb \approx 17 000 µW/cm²=at 38 cm (15") 35w bulb \approx 12 000 µW/cm²=at 38 cm (15")

Visible light 50w: < 5 Lux Visible light 35w: < 3 Lux

Spotlight

Distribution angle (beam) approx. 3.5° Irradiance: 50w bulb > 65 000 μ W/cm²=at 38 cm (15")* 35w bulb > 45 000 μ W/cm²=at 38 cm (15")*

Visible light 50w: < 13 Lux Visible light 35w: < 10 Lux

*Big divergence

Mains - Voltage

- i. 100 -230 VAC
- ii. Operated by separate PSU with self-selecting voltages

Battery

- i. 2 200 mAh Lithium-Ion
- ii. Voltage: 14.8 V
- iii. Running time: 1 hour
- iv. Charging time: 1.5 hours

Weight & Cables

- i. Weight battery operated: 1.9 kilos (4.19 lbs)
- ii. Weight mains operated: 1.4 kilos (3.09 lbs)
- iii. Cable length: 0.7 meters, fully extended 2.8 meters (9 feet)

DISTRIBUTOR:

Handles

- i. Top Handle
- ii. Pistol Handle

Additional Information

- i. Mechanical Stability (bulb): MIL-STD 810
- ii. Service life (bulb): ≈ 2000 hrs
- iii. Wavelength: UV-A, peak-365 nm
- iv. Start-up time: full power after 5-15 sec
- v. Material in housing: Magnesium Alloy
- vi. The housing is via pre milled slots prepared for mounting devices
- vii. CE approved
- viii. EN 62471 Optical Safety: Risk class 3 (High Risk)

Included:

Mains: Lamp, Power Supply unit, UV Block Goggles Battery: Lamp, 1 Battery, UV Block Goggles